Claims

We claim:

- 1. A system for treating a fluid comprising:
- a treatment chamber;
- a light source for emitting light, such that at least a portion of the light travels within the treatment chamber; and
 - a treatment area within the treatment chamber;
- wherein a flow profile of the fluid in the treatment area matches the fluence profile of the light that travels within the treatment area.
- 2. The system of claim 1 wherein the light source is a broad spectrum pulsed light source.
- 3. The system of claim 1 wherein the light source produces at least one wavelength of light between 170nm and 2600nm.
- 4. The system of claim 1 wherein the light source is a continuous wave light source.
- 5. The system of claim 1 wherein the light source is a mercury gas lamp.
 - 6. The system of claim 1 wherein the light source is a pulsed laser.
- 7. The system of claim 1 wherein the light source is internal to the treatment chamber.

- 8. The system of claim 1 wherein the light source is external to the treatment chamber.
- 9. The system of claim 1 further comprising a plurality of baffles coupled to the treatment chamber, wherein the baffles control the flow of fluid within the treatment chamber.
- 10. The system of claim 9 wherein the plurality of baffles provide for substantially uniform treatment of the fluid.
 - 11. A system for the treatment of fluid comprising:
 - a treatment chamber;
- a light source for emitting light, such that at least a portion of the light travels within the treatment chamber; and
- a plurality of transmissive baffles for controlling the flow of fluid within the treatment chamber;

wherein the transmissive baffles allow transmission of the light throughout the treatment chamber preventing biofilm buildup within the treatment chamber.

- 12. The system of claim 11 wherein the light source is a broad spectrum pulsed light source.
- 13. The system of claim 11 wherein the light source produces at least one wavelength of light between 170nm and 2600nm.
- 14. The system of claim 11 wherein the light source is a continuous wave light source.

- 15. The system of claim 11 wherein the light source is a mercury gas lamp.
 - 16. The system of claim 11 wherein the light source is a pulsed laser.
- 17. The system of claim 1 wherein the light source is internal to the treatment chamber.
- 18. The system of claim 11 wherein the light source is external to the treatment chamber.
- 19. The system of claim 11 wherein the plurality of baffles match the flow of fluid to the fluence profile of the light source in at least a portion of the treatment chamber.
 - 20. An apparatus for treating a liquid with light comprising:
 - a treatment chamber;
- a first baffle within the treatment chamber for slowing the velocity of the fluid;
- a second baffle within the treatment chamber for matching the flow of the fluid a fluence profile of light traveling within at least a portion of the treatment chamber; and
- a third baffle within the treatment chamber for maintaining the flow of the fluid throughout a treatment area.
- 21. The apparatus of claim 20 wherein at least a part of the light source is within the treatment chamber.

- 22. The apparatus of claim 20 wherein the light source is outside the treatment chamber.
- 23. A method of treating a fluid comprising:
 inputting the fluid into a treatment chamber;
 exposing the fluid to light from the treatment lamp;
 matching a flow profile of the fluid with a fluence pattern of a light source within at least a portion of the treatment chamber; and
 outputting the fluid from the treatment chamber.
- 24. The method of claim 23 further comprising the steps of:

 providing a first baffle within the treatment chamber designed to slow the fluid velocity;

providing a second baffle within the treatment chamber designed to distribute the flow of the fluid; and

providing a third baffle within the treatment chamber designed to maintain the flow of the fluid through a treatment area.

25. A method of treating fluid comprising:
inputting a fluid into a treatment chamber;
matching a flow profile of the fluid with a fluence pattern of a
treatment lamp; and

outputting the fluid from the treatment chamber.

- 26. The system of claim 25 wherein the treatment lamp produces a broad spectrum pulsed light.
- 27. The system of claim 25 wherein the treatment lamp produces at least one wavelength of light between 170nm and 2600nm.

- 28. The system of claim 25 wherein the treatment lamp produces a continuous wave light.
- 29. The system of claim 25 wherein the treatment lamp is a mercury gas lamp.
- 30. The system of claim 25 wherein the treatment lamp is a pulsed laser.
- 31. The system of claim 25 wherein the treatment lamp is internal to the treatment chamber.
- 32. The system of claim 25 wherein the treatment lamp is external to the treatment chamber.